

ARTFORCE BRISBANE MANUAL



An initiative of Brisbane City Council



TABLE OF CONTENTS


	What to do at a Glance	3
	Forms, Forms and More Forms!!	4
PART 1	Painting Procedures.	5
PART 2	Emergency Procedures	11
PART 3	Site Set-up Diagram.	12
PART 4	Manual Handling Guide	13
PART 5	Colour Mixing Guide	14
PART 6	Weather Check (Resene flyer)	15
PART 7	Paint Prep	17
PART 8	Sticker Removal	18
PART 9	Light Sensor Information	19
PART 10	Documenting Your Artwork Photo Guide	20
PART 11	COVID-19 Direction	24
PART 12	Safety Information – Risk Assessment	25
PART 13	Insurances – Public Liability & Personal Accident	31
PART 14	Paint & Cleaner Product and Safety Data Sheets	34
PART 15	Forms for Signing	67
	A Induction Form	67
	B Pre-Start Safety Checklist	69
	C Still and Moving Image Release Form	72
	D Feedback Survey	74
	E Incident Report Form	75
	F Authority to Paint Notice.	77

What to do at a Glance




Collect your kit

Familiarise yourself with the Artforce Manual



Undertake a pre-painting site visit

Confirm the box ID number and address location



Complete, sign and submit your Induction Form (sample page 67)

Plan your painting day

Mix your colours at home – use only the Resene paint brand provided*

Paint your box

Wear appropriate gear

Complete your Pre-Start Safety Checklist Form (sample page 67)

Set up Work Area (refer diagram page 12)

Prep the box

Prime the box (TSBs only)

Map out your design

Paint the artwork

Sign the artwork

Apply 2 coats of UV Clearcote

Clean up

Recover the site

Dispose of waste and rubbish responsibly

Take photos of your completed artwork (refer page 20)

Complete and sign your Image Release Form (sample page 72)



Return materials


Return signed forms – Induction, Image Release, Pre-Start Safety Checklist

Complete Survey


Return your kit within 5 days of completion



⊗ **Do not use** Posca and other similar paint pens as they run/dissolve under the UV clear top coat.



Forms, Forms and More Forms!!



The following forms are an integral part of our safety requirements and it is important that we retain these for our records.

Please return loose hard copies of all signed forms inside the Artforce Brisbane Manual folder when returning your kit!
Refer to Part 15, pages 67–77, for samples of all our forms.



What:

A Induction Form

B Pre-Start Safety Checklist

C Image Release Form

D Feedback Survey Form

E Incident Report Form

Return:

Complete after collecting equipment pack and undertaking initial site visit and forward copy/image to info@artforbrisbane.com.au

Complete prior to commencing work and forward copy/image to info@artforbrisbane.com.au

Complete, sign and return with kit inside the **Artforce Brisbane Manual folder**.

Complete and return with kit in the **Artforce Brisbane Manual folder**. You can also submit it online [here](#).

Use only if required. Please copy the original from the manual, complete and return as soon as practical after the incident.

And finally:

F An Authority To Paint Notice will be forwarded via email to you and a hard copy can be found in the Artforce Brisbane Manual folder. **Please ensure this is on site with you at all times.**



Painting Procedures



What you need to know: tasks, steps and control measures.

Work Activity: Painting a Traffic Signal Box or Energex Padmount Transformer

Related Risk Assessment: On-site painting

Artforce Brisbane provides:


- High visibility safety vest
- Safety cones x 4 (TSB) x 6 (EPT)
- High quality water-based paint – primer, colours and UV Clearcote
- Mixing containers x 4
- Mixing palette
- Paint prep cleaning agent
- Glue removal product
- Drop sheets x 4 (TSB) x 6 (EPT)
- Tack cloth
- Rags x 2
- Sanding block and paper
- Scraper
- Masking tape
- Acetate sheet x 2 (TSBs only)
- Artforce Brisbane Manual
- Forms for signing and returning
- Mobile equipment box x 1 (TSB) x 2 (EPT)
- Work-in-Progress Notice
- Artforce Brisbane t-shirt

Program participant to provide:

- Paint brushes and rollers
- Water and container/s for cleaning box, brushes, and rollers
- Low seat, safety stool and/or small (2 or 3 step) ladder if available
- Sun safety gear: wide brimmed hat, long sleeve shirt and trousers, closed shoes, sunscreen, sunglasses.
- Water for drinking and snacks/food
- Basic first aid kit which includes bandages, insect repellent and an antidote for bites/stings



TASK	STEPS – WHAT TO DO	RELATED CONTROL MEASURES
Undertake a pre-painting site visit to inspect your box and prepare for painting	<ul style="list-style-type: none"> • Confirm the box ID number and address location. • Ensure the box is located at least 1.5 metres from the kerb. If the box is less than 1.5 metres from the kerb, stop work and contact the Artforce Brisbane Coordinator. • Ensure the box is in good condition - check for rust holes, physical damage, open doors or any shocks or “tingles” when near or touching the cabinet. If any of the above are present, stop work and contact the Artforce Brisbane Coordinator asap. • Make note of how many sides of the box require painting. For example, some boxes are located close to a fence or hedge, preventing access and views to the rear face of the box. Inspect the area around the box. Consider how you will set up your work area, ensuring that the pedestrian thoroughfare is not blocked. • You may wish to take some site photos for your reference. • Familiarise yourself with the nearest amenities. The following website is a helpful resource in locating public amenities: https://toiletmap.gov.au/ • Plan where you will park your vehicle if driving to site and how you will be transporting your materials to site e.g. hand trolley, support person, multiple trips, etc. • Complete and submit your Safety Induction Form. 	<ul style="list-style-type: none"> • Some boxes may be only partially painted as a top section has been added since painting. <u>You will need to paint the entire box.</u> • Some boxes have a label at the base indicating the presence of asbestos. This will refer to the underground footing and does not pose any risk to you and your painting project. • We prioritise the painting of unpainted and partly painted boxes and also boxes painted with existing artworks that are in poor condition. If your box has existing artwork that is still looking good, then please check your box allocation with the Artforce Coordinator. We may have made a mistake! Artforce artworks should last a minimum of 5 years.
Plan your painting day	<ul style="list-style-type: none"> • Consider time of day to paint e.g. not peak hour; early morning or late afternoon to avoid the heat of the day. You may want to plan your painting around the movement of the sun (e.g. work on the western and northern side of the box in the morning, and work on the eastern and southern sides in the afternoon). 	
Mix your colours	<ul style="list-style-type: none"> • Mix your paint colours before travelling to site. Refer to the Colour Mixing Guide Information Sheet (page 14). Thoroughly mix paints to ensure any settled pigment is redispersed before using. 	<ul style="list-style-type: none"> • It is important to keep the screw tops of the paint containers clean and free of paint. Otherwise they will stick shut when the paint dries.
Wear appropriate protective gear	<ul style="list-style-type: none"> • Participants must wear a high visibility safety vest while working. Head, eye, and hand protection are strongly recommended for safety but are not required. • Wear appropriate sun protection: long sleeve shirt and trousers, closed shoes, wide-brimmed hat, sunscreen. 	



TASK	STEPS – WHAT TO DO	RELATED CONTROL MEASURES
Set up your work area	<ul style="list-style-type: none"> • Complete the Pre-Start Safety Checklist • Use safety cones to define your work area. • Cover the space within your work area with drop sheets. • Ensure materials and equipment are placed within the work area where they will not be a trip hazard. • Display the Work-in-Progress Notice. • Do not block the footpath while painting your signal box. Pedestrian traffic must be maintained at all times. • Refer Site Set-up Diagram (page 12) • Follow safe lifting techniques at all times. Use a two person lift or trolley where available; otherwise bend your knees (not your back) and use your leg and abdominal muscles to lift objects. 	<ul style="list-style-type: none"> ⊗ Do not allow anyone other than yourself (the contracted participant) and authorised helper(s) to cross the safety boundary into the work area. It is recommended that you do not have any more than two people painting the box at one time. If necessary, work in alternating shifts. People not painting the box should stand well clear of the defined work area. ⊗ Ensure paint pots have lids on them when not directly in use & are on level ground. ⊗ Keep your Authority to Paint Notice on you at all times.
Prepare the box	<ul style="list-style-type: none"> • If the box is already painted with an artwork design, lightly sand the surface with the sanding block, applying even pressure. The aim is to just dull the existing paint surface so the new primer and paint can better adhere. There is no need to remove the existing paintwork. • Remove the Council applied 'NO POSTERS' stickers, as well as any other non-official stickers, using the supplied scraper and glue removal product (Orange Oil). Use supplied sandpaper if necessary. If removing the 'NO POSTERS' stickers is too difficult, then they can be left and painted over. • Clean the surface of the box with Resene Paint Prep and Housewash (diluted 1:4 in water) using a rag, removing all oil, grease, dirt, loose rust, and loose paint. Then rinse thoroughly with plain water. • Manually dry the surface of the box with a clean rag and allow to thoroughly air-dry. Directly before priming, use the tack cloth to thoroughly remove all dust and fine particles from the surface of the box. • Use low-tack masking tape to mask off areas that must remain unpainted - identification plates, emergency contact phone numbers related to signal operations, hinges, handles, and any of the regulatory or other official notices. For traffic signal boxes, use acetate sheets provided to cover each ID plate, taping around the edges. 	<ul style="list-style-type: none"> ⊗ Do not block or cover vents, keyholes, or light sensors. These are necessary for the ongoing operation of the signal box. Refer to the Light Sensor Information Sheet (page 19). ⊗ Use Resene Paint Prep and Housewash in accordance with the Manufacturer's Product and Safety Data Sheets (pages 34–66).





TASK	STEPS – WHAT TO DO	RELATED CONTROL MEASURES
Prime the box	<ul style="list-style-type: none"> Thoroughly mix the white primer paint to ensure any settled pigment is redispersed before using. Apply a single coat of white primer (undercoat) to all sides of the box that are to feature artwork. Allow to dry. The primer dries to the touch in 30 minutes, and can be recoated in 1 hour. Participants or their designated ‘watchers’ must remain at the site with safety cones in place until paint and coatings have cured to touch or are otherwise safe for public exposure. <p>NOTE: this step is not required for EPTs which are primed by Council. Some primer is included in the EPT equipment box for the removal of any recent graffiti.</p>	<ul style="list-style-type: none"> ✦ <u>Use only the paint supplied.</u> ✦ Apply Zinsser Smart Prime paint in accordance with the Manufacturer’s Product and Safety Data Sheets (pages 34–66). ✦ Apply only when air, material, and surface temperatures are between 10–32°C and the relative humidity is below 85%. <p>NOTE: Artwork is to feature on all accessible sides of the box and not on the top face of the box.</p>
Map out your design	<ul style="list-style-type: none"> Map out your approved artwork design onto the box with paint, pencil, chalk or suitable marker. 	<ul style="list-style-type: none"> ✦ Ensure artwork is faithful to the design approved by Council
Paint the artwork	<ul style="list-style-type: none"> Thoroughly mix paints to ensure any settled pigment is redispersed before using. Apply the colour top coat/s in accordance with your approved artwork design. A single coat only is required, although blue may require a second coat. Allow to dry. Minimum drying time is specified as 45mins at 18°C. Minimum recoat time is specified at 2 hours. Participants or their designated ‘watchers’ must remain at the site with safety cones in place until paint and coatings have cured to touch or are otherwise safe for public exposure. 	<ul style="list-style-type: none"> ✦ <u>Use only the paint supplied.</u> ✦ <u>DO NOT</u> use other paints, especially Posca Pens, as they will run in contact with the UV Clearcote. ✦ Apply Resene colour paints in accordance with the Manufacturer’s Product and Safety Data Sheets (pages 34–66). ✦ Allow paint to dry thoroughly between coats or layers unless you are blending wet-in-wet for a particular effect.
Sign the artwork	<ul style="list-style-type: none"> Select an appropriate area within the artwork to feature your signature. Paint your signature. If your artwork design was produced in consultation with a community group, you may wish to include an acknowledgement – please seek approval for this wording before painting. 	<ul style="list-style-type: none"> ✦ Signatures can be no bigger than 30 x 10cm (actual size) on the box and may include the copyright symbol ©.



TASK	STEPS – WHAT TO DO	RELATED CONTROL MEASURES
Apply UV Clearcote	<ul style="list-style-type: none"> Thoroughly mix the UV Clearcote to before using. Apply two coats of UV Clearcote to all sides of the box that feature artwork. Do not apply in direct hot sunlight. Allow to dry between coats. Minimum drying time is specified as 45mins at 18°C. Participants or their designated ‘watchers’ must remain at the site with safety cones in place until paint and coatings have cured to touch or are otherwise safe for public exposure. 	<ul style="list-style-type: none"> ⊗ Use only the paint supplied. ⊗ Apply Resene UV Clearcote in accordance with the Manufacturer’s Product and Safety Data Sheets (pages 34–66).
Clean up	<ul style="list-style-type: none"> Use rags to clean up any paint spills. Once the paint is dry these can be disposed of in a rubbish bin. The site must be left clean and tidy. All paint spillage onto footpath or surrounding areas must be cleaned up immediately. 	<ul style="list-style-type: none"> ⊗ Clean up spills while still wet and easy to remove. ⊗ Do not wash paint into storm water drains.
Take regular breaks	<ul style="list-style-type: none"> When leaving the site for breaks, ensure the site is clean and tidy, take all valuables with you. To ensure security for your materials and tools, you may wish to keep a line of sight to your work area or leave a ‘watcher’ to mind the site. Plan to remove all working materials and equipment overnight. 	<ul style="list-style-type: none"> ⊗ For personal health and safety, be sure to hydrate frequently and wear sun protection (wide-brimmed hat, long-sleeved shirt and trousers, closed shoes, sunglasses, sunscreen). Take regular rests or meal breaks in shady areas. Carry a first aid kit which includes bandages, insect repellent and an antidote for bites/stings and use as required.
Report Incidents	<ul style="list-style-type: none"> Report any incidents, near misses, dangerous events, serious bodily injuries, or work-caused illnesses to Artforce Brisbane. Serious or major events must be reported to Artforce Brisbane by phoning 0428 095 939 as soon as possible. Please report all incidents, critical and non-critical, by completing the Incident Report Form and returning to Artforce Brisbane via the returned Equipment Pack, email or post. 	<ul style="list-style-type: none"> ⊗ Report incidents as soon as possible
Recover the site	<ul style="list-style-type: none"> Remove all materials, equipment, and any paint residues from the working area. Leave the site in a clean and tidy state. 	
Dispose of waste	<ul style="list-style-type: none"> Do not dump excess paint, paint residue or paint-water into the city sewer system or into the grass or soil around the box. Remove your paint waste and dispose of properly; consult the following for locations: https://recyclingnearyou.com.au/paint/BrisbaneQLD <p>NOTE: You can place empty paint tins with minimal dry paint residue in your recycling bin.</p>	

TASK	STEPS – WHAT TO DO	RELATED CONTROL MEASURES
Take photos of your completed artwork	<ul style="list-style-type: none"> As a minimum, take at least one photograph of each side of the box taken 'straight on' and two 'angled' photographs showing front+side and back+other side to properly document the work. Additional photos of work-in-progress and/or context views are welcome. Refer to the Documenting Your Artwork Photo Guide Information Sheet (page 20) and the Image Release Form (page 72) for further information. Submit photos to the Artforce Brisbane Coordinator. 	<ul style="list-style-type: none"> ⊗ Ensure photos are high resolution and not tightly cropped (i.e. there is some space around the box).
Return Materials	<ul style="list-style-type: none"> Return all materials (less paint), completed forms, and the equipment pack/s to the local Ward Office within 5 days. Refer to the Induction Form for a materials check-list. Ensure materials are clean, in good condition, packed neatly, and are ready for use by the next Artforce Brisbane participant. 	<ul style="list-style-type: none"> ⊗ Please ensure supplied Orange Oil has a fully locked lid and is placed in the zip lock bag provided. Place in the equipment pack in an upright corner position. ⊗ Please do not send rubbish back in your equipment pack.
Complete a feedback survey	<ul style="list-style-type: none"> Complete the online Feedback Survey (if not already completed in hard copy and returned in the equipment pack). 	https://mailchi.mp/artforcebrisbane.com.au/feedbacksurvey





PART 2



Emergency Procedures


What you need to know: steps and key contact information.

Work Activity: Painting a Traffic Signal Box or Energex Padmount Transformer

Related Risk Assessment: On-site painting

EMERGENCY	STEPS (This includes what to do and related control measures)	KEY CONTACT INFORMATION
<ul style="list-style-type: none">⊗ Vehicle accident⊗ Electrical fault⊗ Severe weather – storm, flooding⊗ Fire⊗ Civil disturbance	<p>In an emergency situation follow these instructions:</p> <ul style="list-style-type: none">• Stop work IMMEDIATELY• Assist anyone in the area who may not be familiar with the emergency procedures• Alert the appropriate emergency service authority• Proceed to a safe location and remain there until Emergency Services arrive• Cooperate with those responding to the emergency and follow their instructions• DO NOT delay leaving the work area by looking for belongings or other people• DO NOT obstruct fire hydrants or the responding fire / rescue workers and their equipment• DO NOT re-enter the work area until instructed to do so by Emergency Services• Notify Artforce Brisbane by phone and text message.	<ul style="list-style-type: none">⊗ EMERGENCY SERVICES Police, Fire Brigade, Ambulance Phone: 000⊗ Poisons Centre Phone: 13 11 26⊗ Artforce Coordinator Phone: 0428 095 939
⊗ Medical emergency	<p>In the event of a person being injured:</p> <ul style="list-style-type: none">• Stabilise the person and administer first aid (if competent to do so)• Phone an ambulance (depending on the extent of the injuries)• Notify Artforce Brisbane by phone and text message as soon as practicable.	
⊗ Emergency road works	<ul style="list-style-type: none">• You must immediately make way for any emergency road works related to road safety and/or maintenance of the signal box.• Remove all painting equipment as soon as safely possible and at all times comply with all instructions relating to safety and maintenance given by authorised workers.• Notify the Artforce Coordinator by phone and text message as soon as it is safe to do so.	
⊗ Emergency on or around the signal box site	<ul style="list-style-type: none">• In the event of an emergency on or around the signal box site, you are required to remove all painting equipment as soon as safely possible and at all times comply with all instructions relating to safety and maintenance given by authorised workers.• Notify the Artforce Coordinator by phone and text message as soon as it is safe to do so.	

Site Set-up Diagram




Manual Handling Guide



MANUAL HANDLING

LIFT WITH YOUR LEGS
KEEP YOUR BACK STRAIGHT
KNOW YOUR LIMITS



ASSESS your task FIRST

BEFORE you lift your object plan the route. Clear any obstacles from your path and know where obstacles still lie in an unclear path.




Position your feet apart

Ensure your legs are shoulder width apart for maximum support. Walk in small steps to maintain shoulder width placement.


AVOID lifting overhead or from below knee height

The risk of injury increases when objects are lifted from overhead or below knee height. Avoid storing objects at these heights when possible.



Don't BEND or TWIST while you are lifting or carrying.

Improper bending or twisting could throw you off balance or cause injury.



TIGHTEN your abs

Using your core abdominal muscles will hold you in the proper lifting position and reduce strain on your spine.

LIFT with your LEGS

Bend at the knees & hips not your back - Your leg muscles are stronger than your back and can withstand greater force. This is known as the Semi Squat Technique (Frog lift)

Keep your back STRAIGHT

When you keep your back straight (neutral) your legs carry the majority of the weight making you less likely to injure your back.



HOLD the object at waist level and close to the body

Your arms and your back are better equipped to lift a heavy object at waist level and close to your body than at any other height and/or far from your body.

Use lifting aids

When possible use mechanical aids or get help to lift or carry a heavy load whenever possible. Options include: wheelbarrows, conveyor belts, trolleys, cranes or forklifts.



Two person lifts

When lifting with two or more people ALWAYS ensure people of same size and strength for manual handling tasks.



REDUCE the size of the load when possible

When possible reduce the size of the load or object or make smaller but more frequent trips, e.g. repack a heavy load into smaller parcels.



LIMIT

KNOW your limits!

Ask for help. If you cannot lift an object, don't. Even if the object is not heavy. If it is awkwardly large or unstable, it can be difficult to lift. It is better to wait and ask for assistance than to try and lift something that could potentially cause injury.




Corporate.Work.Health.

































Colour Mixing Guide

We recommend you mix colours at home in preparation for painting your artwork. Please note that the mixes below are a **guide only**. Use tiny amounts of paint to achieve your desired colours using the supplied mixing palette and then apply the same ratio to make up larger quantities for storing in the supplied mixing containers.

When making (blending) colours, only mix the base colours together, limiting the number mixed. This will help to minimise the risk of colour change as different pigments fade at different rates – inorganic pigments such as oxides are more stable than bright organic pigments. The application of Clearcote UVS topcoats will protect the underlying coloured coat by aiding the colour retention of the more vulnerable organic pigments against fading.



 Yellow	+		=		
	+		=		
	+		=		
 Blue	+		=		
	+		=		
	+		=		
 Red	+		=		
	+		=		
	+		=		

 Ochre	+		=		
	+		=		
	+		=		
 Magenta	+		=		
	+		=		
	+		=		
 Red Oxide	+		=		
	+		=		
	+		=		

 +  +  = 

 +  = 

 +  +  =  

 +  =  

Weather Check



Check the weather before painting!



Just what makes the ideal painting day? It's important to get it right or chances are you'll be less than satisfied with the results. 'Ideal' is a tough concept, though – like most things, you're best to aim for moderation.

Common outdoor weather conditions may not appear to be particularly harsh, but they put tremendous demands on exterior paint. The most damaging of these are: sunlight and ultraviolet (U.V.) radiation, water and moisture, and temperature changes.

Higher quality exterior paints help to combat the effects of each of these conditions.



Direct exposure to sunlight (U.V. radiation)

Direct sunshine can degrade the binder and pigment of paint, resulting in chalking, erosion and colour loss. While all paints suffer these effects to some degree, lower quality paints (and interior paints) will generally fail in these ways much earlier than quality exterior paints.

Waterborne paint binders usually resist the effects of direct sunlight better than the binders in solventborne paints, as the waterborne paint binders tend to be 'transparent' to U.V. radiation, while solventborne binders actually absorb the radiation, which breaks them down. Some paint colours, such as bright organic reds and yellows, are more vulnerable to fading caused by U.V. radiation. For these colours, a final coat of **Resene Clearcoat UVS** (see Data Sheet D502) with U.V. inhibitors can help the colours last longer.



Water and moisture

In combination with U.V. radiation, moisture tests the paint's resistance to chalking and fading. Generally higher quality waterborne paints perform better because of the characteristics of the binders they contain.

Changes in the moisture content of the substrate can also cause problems, especially with wood, hardboard and Plywood. When a wet substrate expands or a drying substrate contracts, it can stress the paint, resulting in cracking and flaking. Permeable or 'breathable' waterborne paint allows the water to vaporise and escape. High quality waterborne paints with a high binder content are very flexible, offering added protection against problems with cracking and flaking.

Water and moisture can also cause blistering of exterior paints, and create an environment that is conducive to mould growth. Top quality paints typically contain special additives called fungicides that help prevent mould from forming. **Resene Quick Dry waterborne primer undercoat** (see Data Sheet D45), **Resene TimberLock** (see Data Sheet D48) and **Resene Wood Primer** (see Data Sheet D40) all contain substantial quantities of fungicide for extra protection. Consider asking for **Resene MouldDefender**, a mould inhibitor, to be added to paint being used in mould prone areas to inhibit mould growth. Fungicides inhibit mould growth but do not kill existing mould. Any mould present prior to painting should be treated with **Resene Moss & Mould Killer** (see Data Sheet D80).



Changing humidity

For water to evaporate from a waterborne paint there needs to be some spare room, usually expressed as relative humidity, in the surrounding air for it to go into. Relative humidity tells us how much water vapour there is in the air compared with how much it can actually hold. The ability of the air to hold water vapour lessens dramatically as temperatures fall and the evaporation of water from a paint film may cease altogether with relatively small temperature changes of just 5°C.


At a relative humidity of about 100% water in a waterborne paint film can be likened to a car trying to get onto a busy motorway at peak hour traffic time. There is just so much traffic already there that there is no room for any more cars. At low temperatures water will have little extra energy to get up to the speed necessary to merge in with the traffic. This will lead to easy application – beautiful flow – but there is also a risk of water-sensitive materials accumulating on the surface.

If the temperature drops and the humidity increases, the paint stops losing water. If the temperature change was due the onset of sunset then there are likely to be serious problems with the paint. Any further decrease in temperature will result in dew formation and areas out of direct sunlight will feel the effects of this sooner rather than later. In the very worst case the paint will just not coalesce at all and be washed off by dew. At best the paint's film formation and ability to withstand mild weathering will be compromised. Blistering or surfactant leaching can occur.

Heavier coats of paint will take longer to dry and this will allow more time for temperatures to possibly fall and increase the probability of paint getting caught by high relative humidity.

Decorators should beware of calm, still autumn afternoons when skies are blue, as humidity related problems are more likely.

Low humidity means the air is thirsty for moisture and will grab it, fast, from anywhere – such as a paint film. Low humidity, high temperatures and a porous surface will lead to rapid loss of water and rapid drying. So fast, in fact, that the particles in the film won't have time to arrange themselves properly.




Temperature – Cold

All paints get thick (or more viscous) in the cold and are much harder to use, especially solventborne enamels. One answer is to add thinners, but this has the side-effect of reducing film build and therefore appearance. A better solution is to stand the paint in warm water, which makes it much easier to apply and helps get that smooth, brush mark-free finish that you want.

At lower temperatures solventborne paints will continue to lose solvent but at temperatures about 3°C the chemical cross linking drying process will stop. The solventborne paint will remain soft and be vulnerable to physical damage. When temperatures return to normal the solventborne paint will continue its drying process. Heavily tinted solventborne paints may flatten off in gloss if caught by sudden rises in humidity during the drying process.

Lower temperatures and high humidity will significantly slow down the dry time of waterborne paints. The plastic particles that make up the waterborne binder will harden in the cold to the extent that they can't fuse together to form a film. This can result in cracks forming and sometimes the whole paint film drying to a powder.

The **Resene wintergrade** range of topcoats and primers may be used in temperatures down to 2°C. Do not use when rain, snow or ice is expected, or in warm weather as the wet edge time will be too short to get a good finish.



Temperature – Hot

There will be times when paint is very difficult to apply due to heat, such as on a corrugated iron roof painted dark brown in the middle of a hot summer day. In these conditions, it is best to cease painting. Painting in very hot conditions will result in water evaporating out of the paint very quickly and as a result the paint will thicken up and be very difficult to apply evenly. It will be difficult to keep a wet edge and brush or roller marks will not flow out. Paint brushes will tend to clog up and cans of paint can skin over quite rapidly.

The binder in waterborne paint consists of extremely small spherical particles of solid polymer. When the paint is applied and dries, these particles must fuse together to form a continuous, tough film and bind the pigment particles together. To occur properly, this fusion (or 'coalescence') takes a certain amount of time to occur and requires a certain degree of softness of the binder particles. If the paint is applied under conditions that force it to dry too quickly, it will be impossible for the paint to form a good, durable film even though the paint may look fine.

To help overcome this, **Resene Hot Weather Additive**, which can slow down the drying and give a longer wet edge, can be added to the paint. And if the surface is porous, it can be pre-wetted with water before the application of waterborne paints.

Applying solventborne paints on very hot days generally results in thick wet films that dry rapidly from the top. In these conditions wrinkling on recoat may be a problem.

If you are planning to paint a dark colour and your home is already too hot in summer, consider choosing a **Resene CoolColour™**. A Resene CoolColour is designed to reflect much more of the sun's energy than a standard colour reducing heat buildup.



Inside too

Checking the weather is also important for interior painting. When painting indoors the same rules regarding temperature and humidity still apply – that is, avoid painting in high humidity, low or high temperatures.

Ventilation is important when painting inside to ensure sufficient air circulation to help the paint cure correctly and to allow any solvents that may be released during the drying process to dissipate.



IF THE WASHING ON THE LINE ISN'T DRYING... NEITHER WILL THE PAINT!

So, what is ideal?

15-20°C, humidity 70-80% and a very gentle breeze.

In the absence of the ideal, the following is a useful checklist:

- Is the washing on the line drying? If it's not, neither will your paint.
- If water spilt on a concrete path doesn't dry out, leave your painting until it does.
- If a thin coat of water applied to the substrate has not evaporated in 15 minutes, leave your painting until it does.
- A light breeze is ideal for drying your paint. If it's too windy, your paint will dry too fast, so move operations to a more sheltered side of the building.
- Don't paint in direct sunlight or in extremely hot weather. If you're pushed, paint the shady side of the building or wait until the temperature drops. A good idea is to start ahead of the sun and work your way around the building keeping ahead of the sun as you go.
- Cloudy or overcast conditions are ideal for painting... provided it's not raining and rain is not expected.
- As a general rule apply waterborne paints at temperatures above 10°C and solventborne and industrial paints when the temperature is at least 5°C above the dew point. The lower the temperature the longer the paint will take to dry.
- Read the label on your paint container. If you follow its recommendations, you'll reap the full benefit of the protective capabilities and finish of your paint.

Above – Pages from the Resene 'Check the Weather Before Painting' flyer



Paint Prep



Cleaning painted surfaces with
Resene Paint Prep and Housewash

Resene Paint Prep and Housewash:

- Has a mild detergent so won't stain glass like some other surface cleaning products.
- Is excellent to use with a 3M scouring pad for cleaning around windows (use gloves though).
- Can be used with a soft brush in the same way you would clean a car.
- Can be used either to wash down a painted surface prior to painting or as part of a regular maintenance wash down.

The following photos demonstrate how it works:



**1. Equipment
you'll need**



**2. Mix ratio of
1:4 parts of fresh
water**



**3. Rinse the
area to be
washed.**



**4. Wash with the
mix. A smaller
brush or scouring
pad are ideal for
corners etc.**

5. Leave to dry :)

For more information please visit: <https://www.resene.com.au/products/Paint-Prep-Housewash.htm>



PART 8



Sticker Removal

When cleaning and prepping your Traffic Signal Box prior to painting, remove the Council applied 'NO POSTERS' stickers as well as any other non-official stickers.

To assist with this task your Equipment Box contains:

- Scraper
- Glue removal product (Orange Oil)

It is important to ensure removal of the orange oil prior to painting, as painting must occur on a clean, oil-free surface. Wash down with the supplied Resene Paint Prep and Housewash.

Ensure these items are included when returning the Equipment Box to the local Ward Office.



NOTE: Some 'NO POSTERS' stickers are harder to remove than others. If the stickers are too difficult and time-consuming to remove, then leave and paint over. You are not expected to spend hours trying to remove these stickers.






Light Sensor Information



Light sensors can be found in the recessed space either above the door or on the narrow side of the cabinet as indicated below.

The light sensors are quite small and vary in size from a pin head to a small button. Please ensure you **DO NOT** paint over them.

Not all traffic signal boxes have light sensors.



Examples of Light Sensors

Artwork: Dani Tikel, *Honey I'm Home!*,
Corner Wynnum Rd and Burrai St, Morningside.



Photographing Your Artwork



Photographs of your artwork will be displayed on the Artforce Brisbane website and at the Annual Artforce Awards. They may also be used in the Artforce Brisbane e-newsletter and Brisbane City Council's website, social media, and press releases. It's important to take good quality, high-resolution photographs to showcase your work.

Photos of the completed artwork

Mandatory minimum requirement

- A. One photograph of each side of the box taken 'straight on'. Total of up to 4 photographs.
 - B. Two angled photographs: one showing the front and side of the box; and one showing the rear and other side of the box.
 - C. Two photographs of close-up 'details' of the artwork ie a selected area.
- Please ensure there are no people and no extra things in the photograph to detract from your artwork, such as safety cones, equipment pack, paint pots, water bottles, etc and that all masking tape has been removed. Photographs with equipment or tape will not be accepted.

Photos of the work in progress

Highly desirable

You are strongly encouraged to submit:

- Photographs of yourself posing with the completed artwork.
- Work-in-progress photos, including photos of yourself at work.
- Work-in-progress time-lapse video
- Context photos, including photos with members of the public, friends, family, or neighbourhood dogs [Refer **Image Release Form** – Sample page 72].

Lighting

- Please ensure that the artwork is in good light for photographing.
- Avoid photographing when there are shadows on your artwork. If shade is a problem, wait until the sun is gone and use a flash. If using a flash please avoid the "flash reflection" by taking the photo a little to one side.

File format requirements

- Digital photographs – jpg files are preferred. The minimum size is 1500 x 2000 pixels, approximately 2MB each (minimum).
- Photos in a standard 3 x 4 ratio. Please check the ratio settings on your camera or phone.
- Un-cropped images. Please do not crop photos, ensure there is some space around the box. Photos will be cropped by Artforce Brisbane to suit the display dimensions of the website.
- Please note: sending images from your phone may often compress the image quality. Please ensure to send the highest quality images through your phone.

How to submit your photographs

- Images can be sent to Artforce Brisbane by file-transfer, using programs such as Dropbox, WeTransfer, Hightail, or similar. To assist, Artforce can provide a link to a Dropbox folder on request.
- Images can be sent via email. Emails should be kept to less than 20MB each. It is fine to send multiple emails.
- Images can be placed on a USB data-stick and posted.

There is no limit to the number of photos that you can submit.

Example images: all sides ‘straight on’

Tracey Pearce-Sampson and the Rotary Club of Carindale
Locals Helping Locals. 21 years of Rotary in Carindale. June 2021
 Creek Rd & Meadowlands Rd, Carina



Example images: angles - front & side; back & other side



Example images: details



Example images: context and work-in-progress



≡ Covid 19 Direction ≡



Artforce Brisbane is committed to providing a safe and healthy work environment for all workers, contractors, program participants and members of the public.

In order to comply with government restrictions and help reduce the spread of Corona virus Artforce Brisbane participants are asked to practice good hygiene and social distancing.

Good hygiene

- covering your coughs and sneezes with your elbow or a tissue
- disposing of tissues properly
- washing your hands often with soap and water, including before and after eating and after going to the toilet
- using alcohol-based hand sanitisers
- cleaning and disinfecting surfaces and frequently used objects such as mobiles, keys and wallets



Social distancing

- staying at home when you are unwell
- avoiding large public gatherings
- keeping a distance of 1.5 metres between you and other people whenever possible
- minimising physical contact

Artforce Brisbane is:

- working remotely and practicing social distancing and good hygiene
- cleaning equipment packs and contents with an appropriate cleaning product




To stay up to date with the most recent information on the Corona Virus pandemic please refer to the Queensland Health website:

<https://www.covid19.qld.gov.au/>



Safety Information



Summary of Key Hazards & Risk Assessment.

Risk assessment undertaken by:	Artforce Program Manager
Activity:	Painting a Traffic Signal Box or Energex Padmount Transformer
Equipment:	Refer Artforce Brisbane Manual: Painting Procedures
Participant Advice:	<p>Artforce Program Manager Artforce Brisbane is committed to providing and maintaining a safe and healthy work environment for all workers, contractors, volunteers, visitors and members of the public. Safety is everyone's responsibility. As a worker or volunteer you have a duty to:</p> <ul style="list-style-type: none"> • Follow all safe work practices, procedures, instructions and rules; • Work in a manner which ensures the health and safety of yourself and others; • Encourage other workers/volunteers to work in a healthy and safe manner; • Participate in any relevant training; • Report or rectify any unsafe conditions or incidents that come to your attention. <p>There are a number of hazards involved in painting a Box. This Risk Assessment identifies possible Hazards and potential Risks associated with painting a Box. Control Measures / Actions have been identified to reduce the risk of harm or injury to yourself and/or others. Please read the table on the following pages and note the Actions that are required of you to work safely while painting a Box. If you have any questions or concerns about the risks or actions required of you please contact us.</p> <p>Thank you for taking safety seriously and helping us keep you and others safe.</p>
Person/s at Risk:	<input checked="" type="checkbox"/> Program Participant / volunteer <input checked="" type="checkbox"/> Member of Public <input checked="" type="checkbox"/> On-site Visitor
Other:	<input checked="" type="checkbox"/> Equipment Damage <input checked="" type="checkbox"/> Environment

Safety Information (continued)

Section 1. Summary of key hazards that were identified during the assessment.							
1.	Moving vehicles			2.	Poor cabinet condition		
3.	Exposure to weather conditions			4.	Manual handling and manual work practices		
5.	Exposure to paints and cleaner			6.	Tripping – causing paint spill		
7.	Blocking pedestrian thoroughfare			8.	Exposure to environmental conditions (insects, pollens, etc)		
9.	Abuse, verbal and/or physical			10.	Parking in an undefined area		
Section 2. Risk Assessment (List identified hazards and detail measures taken to address the hazards)							
Identified Hazard	Uncontrolled Risk		Risk Rating	Control Measures / Actions	Controlled Risk		Residual Risk Rating
	Likelihood	Consequences			Likelihood	Consequences	
Moving vehicles on nearby roadway Risk of collision resulting in injury / fatality	Possible	Significant	7	<ul style="list-style-type: none">Box to be painted must be at least 1.5 metres from the edge of road in 40-60km/hr speed zones.Above 60km/hr speed zones the distance to road edge to be determined by the program manager on a 'case-by-case' basis.Consider time of day to paint i.e. not peak hour.Wear the high visibility safety vest provided.Maintain good awareness of the space that you and your equipment is taking up and work within your defined work space.If you feel in danger in any way, stop working and contact Artforce Brisbane asap.	Rare	Significant	5
Poor cabinet condition Risk of electric shock / electrocution	Unlikely	Significant	6	<ul style="list-style-type: none">Routine Council condition reporting and maintenance.Check cabinet for rust holes, physical damage, open doors or any shocks or "tingles" when near or touching the cabinet.	Rare	Significant	5

Safety Information (continued)

				<ul style="list-style-type: none"> If any of the above are present, stop work and contact Artforce Brisbane asap. 			
<p>Exposure to weather – sun and wind</p> <p>Risk of sunburn, windburn, heat stroke, fatigue, dehydration</p>	Almost certain	Moderate	7	<ul style="list-style-type: none"> Wear a wide brim hat, long sleeve shirt and trousers, closed shoes, sunscreen and sunglasses. Drink plenty of water and have regular breaks - every hour. Consider your painting times i.e. perhaps early morning painting is best to avoid the heat of the day. Plan your painting around the movement of the sun (e.g. work on the western and northern side of the box in the morning, and work on the eastern and southern sides in the afternoon). Take rests or meal breaks in shady areas. Consider personal factors (eg general health, medications, etc) and work appropriately to your own constraints, 	Rare	Moderate	3
<p>Exposure to weather: Rain / Storm</p> <p>Risk of electrocution, slips, trips, falls</p>	Possible	Significant	7	<ul style="list-style-type: none"> Do not work in wet weather or storms. Check weather forecast (eg BOM) when planning work. If a storm is imminent or it starts raining during your painting session stop work, pack up the equipment and find shelter. 	Rare	Significant	5
<p>Manual Handling: Lifting, Bending, Moving Equipment</p> <p>Risk of muscle strain, back injury, injured toes</p>	Possible	Moderate	5	<ul style="list-style-type: none"> Use mechanical assistance (eg hand trolley) as required. Two person lift where possible. Use good manual handling practices (see handout provided) including: <ul style="list-style-type: none"> Bend your knees (not your back) to lift equipment. Avoid twisting motions while lifting equipment. Remove heavier items from the Pack and carry separately to reduce the weight of the Pack if you find it too heavy. Wear closed shoes. 	Rare	Moderate	3
<p>Ergonomics – manual work.</p> <p>Risk of muscle strain, over-exertion, fatigue</p>	Possible	Moderate	5	<ul style="list-style-type: none"> Take regular breaks - every hour. Do not overextend or hold your body in awkward positions Use a low seat or stool so you can sit and paint lower areas of the box. Use a small, (3 step) step ladder on even ground to reach areas of the box that are above shoulder height. 	Rare	Moderate	3

Safety Information (continued)

Paint and Surface Cleaner exposure Risk of eye, skin and respiratory irritation	Possible	Minor	4	<ul style="list-style-type: none"> Use paint brushes and brush on paint to minimise risk of airborne paint and exposure to eyes and contact with skin. If you have particularly sensitive skin you may wish to wear gloves or a barrier cream. Use paints and cleaning product in accordance with instructions on Safety Data Sheets supplied (pages 34–66) and follow relevant first aid measures, including for skin and eye contact, inhalation and ingestion. 	Unlikely	Minor	3
Tripping – causing paint spill Risk of injury and harm to the environment	Almost certain	Minor	6	<ul style="list-style-type: none"> Ensure paint pots are placed where they will not be a trip hazard. Ensure paint pots have lids on them when not directly in use and are on level ground. Use drop sheets to prevent ground and storm water contamination. Use rags to clean up any paint spills as soon as practicable. Once the paint is dry these can be disposed of in a rubbish bin. 	Unlikely	Minor	3
Blocking pedestrian thoroughfare Risk of injury or fatality to pedestrians	Likely	Significant	8	<ul style="list-style-type: none"> Set up work area as per the Site Set-Up Diagram (page 12) ensuring you are not blocking the pedestrian thoroughfare. Do not have any more than two people painting the box at one time. If necessary work in alternating shifts. People not painting the box should stand well clear of the defined work space. 	Rare	Significant	5
Exposure to environment: spider, insect, or snake bites & grass or pollen Risk of allergic reactions	Likely	Moderate	6	<ul style="list-style-type: none"> Inspect site for hazards by completing the Pre-Start Safety Checklist provided. Carry a first aid kit which includes bandages, insect repellent and an antidote for bites / stings and use as required. If you suffer from hay-fever / allergies address this potential risk as directed by your medical practitioner. Call Emergency Services 000 if you require or feel you require immediate assistance. 	Unlikely	Moderate	4

Safety Information (continued)

Negative interaction with members of the public Risk of verbal and/or physical abuse	Likely	Minor	5	<ul style="list-style-type: none"> The majority of artists' experiences with the public are positive but please be aware that some members of the public may think you are doing something illegal or may simply not appreciate your efforts. Display the Work-in-Progress sign within the workspace. Have your Authority to Paint Notice to hand to show you are authorised to paint. If member of the public challenges the validity of these notices, advise them to contact Artforce Brisbane. If you feel in any danger, cease work immediately, pack up equipment (if safe to do so, otherwise leave in place), leave the site and contact Artforce Brisbane as soon as possible. Call Emergency Services 000 if you require or feel you may require immediate assistance. 	Unlikely	Minor	3
Parking vehicle near work site in an undefined parking area. Risks of injury to pedestrians, distress to property owners, damage to vehicle.	Likely	Moderate	6	<ul style="list-style-type: none"> You must park your vehicle in accordance with road and parking regulations. 	Rare	Insignificant	1

SIGN-OFF	Artforce Program Manager:		14/01/25
----------	---------------------------	---	----------

Safety Information (continued)

1. CONSEQUENCE / IMPACT CRITERIA			Consequence / Impact Ratings				
Description			(Where an event has more than one 'Loss Type', choose the 'Consequence / Impact' with the highest rating. If 'Near Miss' select potential rating).				
			Insignificant	Minor	Moderate	Major	Significant
Health and Safety			No treatment required	First aid treatment required	Medical treatment required	Lost time injury to worker, injury to member of the public or permanent injury or disability (public or workers)	One or more fatalities (public or workers)
Environmental			Limited or no environmental damage with no intervention required	Limited or minor damage requiring possible intervention	Environmental impact requiring treatment inside or outside site	Serious environmental harm requiring restoration and/or remediation inside or outside of site with possible regulatory intervention	Permanent/material damage to environment requiring ongoing remediation and monitoring with regulatory involvement and possible further enforcement action
Reputational			Slight impact- public awareness may exist but no public concern.	Limited impact- local public concern.	Considerable impact- regional public concern. Client unease.	National public concern. Leads to share price volatility. Loss of client.	International public attention. Direct impact on share price. Loss of core client.
2. LIKELIHOOD / PROBABILITY & RISK RATING			Risk Rating				
Likelihood / Probability	Examples (Near-misses as well as actual events)	% chance of occurring					
Almost Certain	The unwanted event has occurred frequently; occurs in order of one or more times per year & is likely to reoccur within 1 year	75% - 99%	5	6	7	8	9
Likely	The unwanted event has occurred infrequently; occurs in order of less than once per year & is likely to reoccur within 5 years	50% - 74%	4	5	6	7	8
Possible	The unwanted event has happened in the business/industry at some time; or could happen within 10 years	25% - 49%	3	4	5	6	7
Unlikely	The unwanted event has happened in the business/industry at some time; or could happen within 20 years	11% - 24%	2	3	4	5	6
Rare	The unwanted event has never been known to occur in the business/industry; or it is highly unlikely that it will occur within 20 years	0 - 10%	1	2	3	4	5

Risk Level: **Extreme:** NO WORK TO BE CONDUCTED **High:** Requires Brisbane City Council sign-off **Medium:** Requires Artforce Manager sign-off **Low:** Monitor

Insurances – Public Liability & Personal Accident

Certificate of Currency



Liberty
Specialty Markets

This certificate confirms that the undermentioned policy is current as at the date shown below.

PRODUCT NAME	Group Personal Accident and Sickness
POLICY NUMBER	2000149960
ISSUED	06 December 2024
INSURED	Elizabeth Jackson
NAMED ADDRESS	15 York street, Morningside, QLD, 4170
BROKERAGE	BMS Risk Solutions Pty Ltd
BROKERAGE ADDRESS	Level 6, The Annex, 12 Creek St, Brisbane, QLD 4000, Australia
POLICY PERIOD	From: 09 December 2024 at 4pm local standard time To: 09 December 2025 at 4pm local standard time (both dates inclusive)
POLICY WORDING	Liberty AU Group Personal Accident and Sickness PDS and Policy Wording - Nov 2021(a)
OPERATIVE TIME	As per Schedule of Benefits
DOES AN AGGREGATE DEDUCTIBLE APPLY TO THIS RISK?	No

Certificate of Currency

p.2 of 3

SCHEDULE OF BENEFITS

CATEGORY	1		
INSURED PERSONS	All voluntary workers of the insured only		
OPERATIVE TIME	Voluntary workers		
SECTION			BENEFIT PAYABLE / SUM INSURED
PART A	DEATH AND CAPITAL BENEFITS		\$100,000
PART B	FRACTURED BONES		\$2,500
PART C	LOSS OF INCOME – WEEKLY INJURY BENEFIT	100% of Income up to	\$1,000
		Benefit Period	104 weeks
		Excess Period	7 days
PART D	LOSS OF INCOME – WEEKLY SICKNESS BENEFIT		Not Insured
PART E	INJURY – SURGICAL BENEFITS OVERSEAS	As per Policy	
PART F	SICKNESS – SURGICAL BENEFITS OVERSEAS	Not Insured	
PART G	DENTAL INJURY	As per Policy	
PART H	NON MEDICARE MEDICAL EXPENSES	90% of expenses up to	\$2,500
		Excess	\$100

Certificate of Currency


p.3 of 3

Policy Aggregate Limits of Liability

Personal Accident	Any One Occurrence	\$1,000,000
	Non Scheduled Flying	\$500,000

This Certificate:

- Is issued as a matter of information only and confers no rights upon the holder
- Does not amend, extend or alter the coverage afforded by the policy listed
- Is only a summary of the cover provided
- Reference must be made to the current policy wording for full details
- Is current at the date of issue only
- Please contact CSN on +61 2 8256 1770 for assistance with all claims



Paint and Cleaner Product & Safety Data Sheets



A compilation of documents courtesy of paint suppliers.



Resene Paint Prep and Housewash (continued)

Resene Paint Prep and Housewash Safety Data Sheet

RESENE PAINT PREP & HOUSEWASH- CONCENTRATE

Resene Paints Ltd

Version No: 1.1

Safety Data Sheet according to HSNO Regulations

Issue Date: 11/06/2020

Print Date: 11/06/2020

L.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	RESENE PAINT PREP & HOUSEWASH- CONCENTRATE
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	9834
--------------------------	------

Details of the supplier of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 2 9186 1132


Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification [1]	Eye Irritation Category 2, Chronic Aquatic Hazard Category 3, Skin Corrosion/Irritation Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.3B, 6.4A, 9.1C

Label elements

Hazard pictogram(s)	
SIGNAL WORD	WARNING

Hazard statement(s)

H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
H316	Causes mild skin irritation.

Precautionary statement(s) Prevention

P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
----------------	--

Resene Paint Prep and Housewash Safety Data Sheet (continued)

P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
13845-36-8	1-10	potassium triphosphate
84133-50-6	1-10	alcohols C12-14 secondary ethoxylated

SECTION 4 FIRST AID MEASURES**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay if pain persists or recurs. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	If aerosols, fumes or combustion products are inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop seek medical attention.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES**Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
-----------------------------	-------------

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Resene Paint Prep and Housewash Safety Data Sheet (continued)

Minor Spills	<p>► Clean up all spills immediately.</p> <p>Control personal contact with the substance, by using personal protective equipment. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean- up.</p>
Major Spills	<p>Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.</p>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE**Precautions for safe handling**

Safe handling	<p>► Avoid unnecessary personal contact, including inhalation.</p> <p>► DO NOT allow clothing wet with material to stay in contact with skin</p>
Other information	

Conditions for safe storage, including any incompatibilities

Suitable container	► Polyethylene or polypropylene container.
Storage incompatibility	None known

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
RESENE PAINT PREP & HOUSEWASH-CONCENTRATE	Not Available	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
potassium tripolyphosphate	Not Available	Not Available
alcohols C12-14 secondary ethoxylated	Not Available	Not Available

OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
potassium tripolyphosphate	E	≤ 0.01 mg/m³


Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	► Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	<p>► Wear chemical protective gloves, e.g. PVC.</p> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.</p>
Body protection	See Other protection below
Other protection	► Overalls.

Resene Paint Prep and Housewash Safety Data Sheet (continued)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Thin foamy, pale yellow, clear liquid		
Physical state	Liquid	Relative density (Water = 1)	1.03-1.05
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	11	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	97
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	105

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	► Unstable in the presence of incompatible materials.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'.
Skin Contact	Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.
Chronic	Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

RESENE PAINT PREP & HOUSEWASH-CONCENTRATE	TOXICITY	IRRITATION
	Not Available	Not Available
potassium tripolyphosphate	TOXICITY	IRRITATION
	Oral (rat) LD50: ~2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1] Skin: no adverse effect observed (not irritating) ^[1]

Resene Paint Prep and Housewash Safety Data Sheet (continued)

alcohols C12-14 secondary ethoxylated	TOXICITY		IRRITATION	
	Not Available		Not Available	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances			
ALCOHOLS C12-14 SECONDARY ETHOXYLATED	<p>Polyethers, for example, ethoxylated surfactants and polyethylene glycols, are highly susceptible towards air oxidation as the ether oxygens will stabilize intermediary radicals involved.</p> <p>Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products .</p> <p>Alcohol ethoxylates are according to CESIO (2000) classified as Irritant or Harmful depending on the number of EO-units:</p> <p>EO < 5 gives Irritant (Xi) with R38 (Irritating to skin) and R41 (Risk of serious damage to eyes)</p> <p>EO > 5-15 gives Harmful (Xn) with R22 (Harmful if swallowed) - R38/41</p> <p>EO > 15-20 gives Harmful (Xn) with R22-41</p> <p>>20 EO is not classified (CESIO 2000)</p> <p>Oxo-AE, C13 EO10 and C13 EO15, are Irritating (Xi) with R36/38 (Irritating to eyes and skin) .</p> <p>AE are not included in Annex 1 of the list of dangerous substances of the Council Directive 67/548/EEC</p> <p>In general, alcohol ethoxylates (AE) are readily absorbed through the skin of guinea pigs and rats and through the gastrointestinal mucosa of rats.</p> <p>For high boiling ethylene glycol ethers (typically triethylene- and tetraethylene glycol ethers):</p> <p>Skin absorption: Available skin absorption data for triethylene glycol ether (TGBE), triethylene glycol methyl ether (TGME), and triethylene glycol ethylene ether (TGEE) suggest that the rate of absorption in skin of these three glycol ethers is 22 to 34 micrograms/cm2/hr, with the methyl ether having the highest permeation constant and the butyl ether having the lowest.</p>			
RESENE PAINT PREP & HOUSEWASH-CONCENTRATE & POTASSIUM TRIPOLYPHOSPHATE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases.			
POTASSIUM TRIPOLYPHOSPHATE & ALCOHOLS C12-14 SECONDARY ETHOXYLATED	No significant acute toxicological data identified in literature search.			
Acute Toxicity	✗	Carcinogenicity	✗	
Skin Irritation/Corrosion	✓	Reproductivity	✗	
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗	
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗	
Mutagenicity	✗	Aspiration Hazard	✗	
Legend: ✗ – Data either not available or does not fill the criteria for classification ✓ – Data available to make classification				

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

RESENE PAINT PREP & HOUSEWASH-CONCENTRATE	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
potassium tripolyphosphate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	EC50	48	Crustacea	>100mg/L	2
	EC50	96	Algae or other aquatic plants	69.2mg/L	2
alcohols C12-14 secondary ethoxylated	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
------------	-----------------

Resene Paint Prep and Housewash Safety Data Sheet (continued)

No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS**Waste treatment methods**

Product / Packaging disposal	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ Recycle wherever possible. <p>Consult manufacturer for recycling option.</p> <p>Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.</p>
-------------------------------------	---

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 TRANSPORT INFORMATION**Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture**

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002530	Cleaning Products (Subsidiary Hazard) Group Standard 2017

POTASSIUM TRIPOLYPHOSPHATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)**ALCOHOLS C12-14 SECONDARY ETHOXYLATED IS FOUND ON THE FOLLOWING REGULATORY LISTS**

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)**Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Resene Paint Prep and Housewash Safety Data Sheet (continued)

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (potassium triphosphate; alcohols C12-14 secondary ethoxylated)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (alcohols C12-14 secondary ethoxylated)
Japan - ENCS	No (alcohols C12-14 secondary ethoxylated)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	No (alcohols C12-14 secondary ethoxylated)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	11/06/2020
Initial Date	28/09/2017

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.
The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.

Zissner® SmartPrime®

Water-based modified acrylic primer/sealer, stain killer and bond coat.

DESCRIPTION AND USES

Zissner® SmartPrime® is a water-based modified acrylic primer/sealer, stain killer and bond coat. This product provides the characteristics of an oil-based product in an all-purpose water-based interior/exterior primer. SmartPrime was developed for professional and commercial applications, combining stain blocking power, fast-dry convenience, excellent flow and leveling, and excellent adhesion to glossy surfaces.

It is suitable for use on residential, institutional or commercial use in schools, hospitals, hotels, nursing homes, restaurants, etc. Apply to interior and exterior walls, ceilings, doors, trim, fascia, soffits, foundations, railings, and related paintable surfaces. SmartPrime adheres to wood, plaster, concrete, gloss enamels, hardboard, glass and tile.

For interior surfaces, apply to new and previously painted drywall, plaster, wood (pine, fir, cedar, redwood, plywood), metal (aluminum, stainless steel, galvanized metal), vinyl, PVC, fiberglass and masonry (stucco, concrete block, concrete, brick). For exterior surfaces, apply to new or previously painted wood (pine, fir, cedar, redwood, T-111, plywood, pressure-treated wood), hardboard, glass, metal (aluminum, stainless steel galvanized metal), PVC, rigid plastics, aluminum and vinyl siding, fiberglass and masonry (stucco, concrete block, concrete, brick).

SmartPrime penetrates to seal porous surfaces to provide a smooth and even finish so topcoat paints have better coverage and more consistent sheen. Smart Prime blocks stains from water, smoke, cedar or redwood bleed, grease, handprints, asphalt, crayon, graffiti and rust stains.

MPI #6, #39, #50, #137, #149 Certified*

PERFORMANCE CHARACTERISTICS

- Bonds to glossy surfaces without scuff sanding
- Formulated with proprietary stain-blocking resins
- Dried film is mold and mildew resistant
- Bonds to moderately chalky surfaces
- Dries in minutes, can be recoated in 1 hour

PRODUCTS

SKU	DESCRIPTION
249727	1 Quart
249728	5 Gallons
249729	1 Gallon

* Refer to the MPI website for the most current listing of MPI certified products.

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper adhesive, or any contamination that may interfere with adhesion. If unsure of cleanliness, always wash surface with household ammonia and water solution, appropriate cleaning solution or solvent (do not use TSP as a cleaner). Remove any peeling and/or unsound coatings. Sand any remaining paint film edges smooth with the surface. Remove existing stains by washing, sanding, scraping, etc. Countersink exposed nail heads, spot prime and fill all nail holes and gouges with Ready-Patch® spackling compound or equally suitable material. Lightly sand exposed exterior wood with 80 to 100 grit sandpaper to remove loose or weathered wood fibers.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

NEW DRYWALL

New drywall must be wiped down with a damp cloth to remove residual joint compound dust prior to priming.

PLASTER & CONCRETE

New plaster must age 30 days before application of SmartPrime. Concrete, plaster, masonry and related surfaces must be fully cured before priming.

DAMAGED DRYWALL

Damaged drywall should be repaired prior to priming. Spot prime area of torn drywall facing paper or exposed gypsum core with GardZ® Problem Surface Sealer and then skim coat with drywall mud before priming the total area with SmartPrime.

Zissner® SmartPrime® (continued)

PRODUCT APPLICATION (cont.)**SURFACE PREPARATION (cont.)****MOLD & MILDEW**

Remove interior mildew stains by washing the surface with a solution of one cup household bleach in a gallon of water. Follow label instructions and personal protection recommendations on the MSDS. Do not add ammonia or other cleaning products to the bleach solution. Kill exterior mildew with Jomax® House Cleaner and Mildew Killer. If concerned about mold and mildew behind walls, underneath flooring, in ventilation systems or other unseen areas, contact a professional who specializes in mold and mildew remediation. For commercial buildings and schools, follow appropriate guidelines for mold removal.

STAINS

Remove existing stains by washing, sanding, scraping, etc. Water stains, stains from water-based markers and smoke stains should be primed with B-I-N Primer/Sealer. Nicotine stains should be primed with Cover-Stain®.

STAIN BLOCKING

Blocks stains from water, smoke, cedar or redwood bleed, grease, handprints, asphalt, crayon, graffiti and rust stains. Make sure all water leaks are repaired before applying SmartPrime to a water stain. If the area requires patching, apply SmartPrime before and after applying the spackling or patching compound. After applying SmartPrime to the stain, the stain may appear in the primer film. This is normal. The stain will be locked in the primer film and will not bleed into the topcoat. Allow 2 hours to dry for interior stain blocking and overnight for bare cedar or redwood. Certain applications may require a second coat of primer. Prime severe water and smoke stains and block associated odors with Zinsser B-I-N Shellac Base Primer Stain Blocker.

METAL SURFACES

Use SmartPrime to prime uncoated ferrous metals, galvanized metal, aluminum, or previously painted ferrous metals.

WOOD

Lightly sand exposed exterior wood with 80-100 grit sandpaper to remove loose or weathered wood fibers. For new Cedar and Redwood applications, allow SmartPrime to dry 24 hours before painting or topcoating. Sand interior bare wood surfaces using medium to fine grit sandpaper.

LIMITATIONS

Smart Prime is not recommended for application to floors, decks, roof surfaces or any surface subject to immersion or prolonged contact with water.

PRODUCT APPLICATION (cont.)**APPLICATION**

Apply only when air, material, and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is below 85%. Substrate moisture should not exceed 12%. Thoroughly mix to ensure any settled pigment is re-dispersed before using. In most cases only one coat is necessary to prime most surfaces. If excessive absorption occurs over very porous substrates a second coat may be necessary. Spot priming is recommended only under high-hiding topcoat finishes. For best results, prime entire surface before painting. Keep container closed when not in use. Apply with a synthetic (nylon, polyester or blend) bristle brush, roller, or airless sprayer. Follow manufacturer's instructions when using spray equipment. For airless spraying use a .017" tip at 2000 to 2500 psi. If a conventional sprayer is used, spray at 50-60 psi. Wear NIOSH approved respirator and provide adequate ventilation.

THINNING

If thinning is necessary, add no more than 10 fluid ounces of clean water per gallon and mix thoroughly. Thinning the primer may affect its stain-blocking properties.

TINTING

SmartPrime may be tinted with up to 2 ounces of universal colorant per gallon. Tinting the primer toward the color of the topcoat helps hide in one coat. For mid or deep tone colors use Bulls-Eye 1-2-3 Deep Tint. Note: The addition of universal colorant may prolong the dry time of this product.

DRY TIME

Dries to the touch in 30 minutes, can be recoated in 1 hour. The primer film develops full adhesion and hardness after it cures in 7 days. Lower temperatures, higher humidity, and the addition of tint will prolong dry and cure time. Allow more time at cooler temperatures.

CLEAN-UP

Clean up spills and paint drips with detergent and warm water. If spills or drips have dried, use denatured alcohol or ammoniated detergent to soften and remove primer. Wash application tools in detergent and warm water immediately use. Follow equipment manufacturer's directions to clean spray equipment. Dispose of unused or unwanted product in accordance with local laws regulating water-based coatings.

Zissner® SmartPrime® (continued)

PHYSICAL PROPERTIES

		SMARTPRIME
Resin Type		Water-based Acrylic
Pigment Type		Titanium Dioxide
Solvents		Water, Glycol Ethers
Weight	Per Gallon	10.8 lbs.
	Per Liter	1.29 kg
Solids	By Weight	50.9%
	By Volume	35.2%
Volatile Organic Compounds		<25 g/l (0.21lbs/gal.)
Recommended Dry Film Thickness (DFT) per Coat		1.0-1.5 mils (25-37.5µ)
Wet Film to Achieve DFT (Unthinned material)		3.0-4.0 mils (75-100µ)
Practical Coverage at Recommended DFT (assume 15% material loss)		Approximately 400 sq.ft./gal. (9.8 m ² /l) depending on application method and surface porosity
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	30 minutes
	Recoat	1 hour
	Full Cure	7 days
Shelf Life		5 years
Flash Point		>200°F (93°C)
Flame Spread (ASTM-84-97A)		Class A
Smoke Contrib. (ASTM-84-97A)		Class A
Storage		Store indoors at 40-90°F (4-32°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

Zissner® SmartPrime® (continued)

Zissner® SmartPrime® Safety Data Sheet

Safety Data Sheet



www.rustoleum.com.au

1. Identification

Product Name:	ZINSSR 1L 6PK AUS SMART PRIME	Revision Date:	5/21/2019
Name on Label:	Smart Prime	Supersedes Date:	11/1/2018
Product Identifier:	259336		
Product Use/Class:	Primer/WB Acrylic		
Supplier:	Rust-Oleum Australia & New Zealand Pty Ltd 8 Lakeview Drive Scoresby, Melbourne, Victoria 3179 Australia Ph 1 300 784 476	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
Preparer:	Regulatory Department		
Emergency Telephone:	24 Hour Hotline: 1-300-366-961		

2. Hazard Identification

This product is not classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

Classification**Symbol(s) of Product**

Not a hazardous substance or mixture per Safe Work Australia criteria.

Signal Word

No Signal Word has been assigned.

Possible Hazards

24% of the mixture consists of ingredient(s) of unknown acute toxicity.

3. Composition/Information On Ingredients**HAZARDOUS SUBSTANCES**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt.% Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Titanium Dioxide	13463-67-7	10-25	Not Available	Not Available
Hydrous Magnesium Silicate	14807-96-6	10-25	Not Available	Not Available
Barium Sulfate	7727-43-7	2.5-10	GHS07	H332
Zinc Oxide	1314-13-2	0.1-1.0	Not Available	Not Available
2,4,7,9-Tetramethyl-5-Decyne-4,7-Diol	126-86-3	0.1-1.0	GHS05-GHS07	H302-312-317-318
Ethylene Glycol	107-21-1	0.1-1.0	GHS07	H335

Zissner® SmartPrime® Safety Data Sheet (continued)

The balance of the product is Nonhazardous.

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, rinse mouth with water. If feeling unwell, get medical attention. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

5. Fire-fighting Measures

ADG HAZCHEM CODE: Not Hazardous

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing. Avoid contact with eyes.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep from freezing. Keep container closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	WHS WES TLV-TWA	WHS WES TLV-STEL
Titanium Dioxide	13463-67-7	15.0	10 mg/m3	N.E.
Hydrous Magnesium Silicate	14807-96-6	15.0	2 mg/m3	N.E.
Barium Sulfate	7727-43-7	5.0	5 mg/m3	N.E.
Zinc Oxide	1314-13-2	1.0	2 mg/m3	10 mg/m3
2,4,7,9-Tetramethyl-5-Decyne-4,7-Diol	126-86-3	1.0	N.E.	N.E.
Ethylene Glycol	107-21-1	1.0	25 ppm	50 ppm

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

Zissner® SmartPrime® Safety Data Sheet (continued)

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications. Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Solvent Like	Odor Threshold:	N.E.
Specific Gravity:	1.317	pH:	N.D.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Miscible	Partition Coefficient, n-octanol/water:	N.D.
Decomposition Temp., °C:	N.D.	Explosive Limits, vol%:	N.A. - N.A.
Boiling Range, °C:	100 - 537	Flash Point, °C:	94
Flammability:	Does not Support Combustion	Auto-ignition Temp., °C:	N.D.
Evaporation Rate:	Slower than Ether	Vapor Pressure:	N.D.
Vapor Density:	Heavier than Air		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid contact with strong acid and strong bases.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalis.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation. Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	2500 mg/kg	N.E.
14807-96-6	Hydrous Magnesium Silicate	6000	N.E.	30
7727-43-7	Barium Sulfate	307000 mg/kg Rat	N.E.	N.E.
1314-13-2	Zinc Oxide	>5000 mg/kg Rat	N.E.	N.E.
126-86-3	2,4,7,9-Tetramethyl-5-Decyne-4,7-Diol	>500 mg/kg Rat	>1000 mg/kg Rabbit	N.E.
107-21-1	Ethylene Glycol	4700 mg/kg Rat	10600 mg/kg Rat	N.E.

Zissner® SmartPrime® Safety Data Sheet (continued)

N.E. - Not Established

12. Ecological Information**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.**13. Disposal Information****DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.**14. Transport Information**

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>ADG</u>
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No
ADG Hazchem Code:	Not Hazardous			

15. Regulatory Information**Montreal Protocol**

No Montreal Protocol components exist in this product.

Stockholm Convention

No Stockholm Convention components exist in this product.

Rotterdam Convention

No Rotterdam Convention components exist in this product.

MARPOL

This product contains the following substances listed under the MARPOL regulations:

<u>Chemical Name</u>	<u>CAS-No.</u>
Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl Ester	10605-21-7

SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

<u>Chemical Name</u>	<u>Schedule Number(s)</u>
3-Iodo-2-Propynyl Butyl Carbamate	Schedule 5

Zissner® SmartPrime® Safety Data Sheet (continued)

Capital Territories Environmental Regulations

This product contains the following substances listed under the Australian Capital Territories Environmental Protection Regulation:

<u>Chemical Name</u>	<u>Schedule</u>	<u>Schedule Name</u>
Chlorite Mineral	4	DOM - Disinfection By-products
Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl Ester	3	DOM - Pesticides

16. Other Information

SDS REVISION DATE: 5/21/2019

REASON FOR REVISION: Product Composition Changed
Substance and/or Product Properties Changed in Section(s):
02 - Hazard Identification
15 - Regulatory Information
Revision Statement(s) Changed

Legend:

N.A. - Not Applicable N.D. - Not Determined N.E. - Not Established
S.T.E.L. - Short Term Exposure Limit
T.W.A. - Time Weighted Average
W.E.S. - Workplace Exposure Standard
W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Resene Lumbersider Paint

Waterborne – Low Sheen

Resene Lumbersider is based on a tough 100% acrylic resin to ensure maximum durability in all exposed conditions.
Imparts a natural low sheen look that is fully washable.

	PHYSICAL PROPERTIES
Vehicle type	100% acrylic
Pigmentation	Titanium dioxide/fillers
Solvent	Water
Finish	Low sheen
Colour	Selected Resene Total Colour System, including BS5252, Multi-Finish, Whites & Neutrals and The Range
Dry time (min)	45 minutes at 18°C
Recoat time (min)	2 hours
Primer required	Yes, dependent on surface
Theoretical coverage	12 sq. metres per litre
Dry film thickness	33 microns at 12 sq. metres per litre
Usual no. of coats	2; some colours may require an additional coat
Abrasion resistance	Very good
Chemical resistance	Good
Heat resistance	Thermoplastic
Solvent resistance	Good
Durability	Excellent
Thinning and clean up	Water
VOC	c. 35 grams per litre (see Resene VOC Summary)

Performance and limitations

PERFORMANCE

- Excellent adhesion to primed and natural substrates, timber, concrete and old paintwork.
- Excellent as a roof coating where a low sheen finish is required.
- May be used on surfaces that are to be used for the collection of drinking water.
- Low sheen, highly scrubbable wall paint.
- An Environmental Choice approved product.

LIMITATIONS

- Do not apply at temperatures below 10°C or when it is liable to drop below 10°C during the drying period.

Resene Lumbersider (continued)

Surface preparation


- Clean down thoroughly to remove all dirt, dust and loose material. Ensure surface is free from oil, grease and mould.

Application

- Apply by brush, speed brush, synthetic fibre roller or spray.
- Apply two coats Resene Lumbersider allowing at least two hours between coats.

For more information please visit: www.resene.com

View Data Sheets online at www.resene.com/datasheets.



Resene Lumbersider (continued)

Resene Lumbersider Safety Data Sheet

RESENE LUMBERSIDER

Resene Paints Ltd

Version No: 1.1

Safety Data Sheet according to HSNO Regulations

Issue Date: 11/02/2020

Print Date: 11/02/2020

L.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	RESENE LUMBERSIDER
Synonyms	Incl. White, Pastel, Light, Mid, Deep, Ultra Deep, Ochre, Green, Black, Magenta, Light Grey, Winter Grade White, Yellow 2, Rich Red, Intense Red, Cool Black, HO Cool Black.
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	10470 10330 10331 10332 10333 10334 10341 10342 10567 10345 10349 10415 10346 10347 10348 10580 8968
--------------------------	--

Details of the supplier of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 2 9186 1132

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification [1]	Acute Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	9.1D

Label elements

Hazard pictogram(s)	Not Applicable
SIGNAL WORD	NOT APPLICABLE

Hazard statement(s)

H402	Harmful to aquatic life.
------	--------------------------

Precautionary statement(s) Prevention

P273	Avoid release to the environment.
------	-----------------------------------

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation
------	---

Resene Lumbersider Safety Data Sheet (continued)

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017 to be identified:

Mixtures

CAS No	%[weight]	Name
25265-77-4	<2	2,2,4-trimethyl-1,3-pentanediol monoisobutyrate

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> Avoid contamination with oxidising agents
----------------------	---

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	<ul style="list-style-type: none"> Non Combustible. <p>Decomposes on heating and produces toxic fumes of: carbon dioxide (CO₂) other pyrolysis products typical of burning organic material.</p>

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Control personal contact with the substance, by using personal protective equipment. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean-up.
Major Spills	Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

Resene Lumbersider Safety Data Sheet (continued)

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	▶ Avoid unnecessary personal contact, including inhalation.
Other information	▶ Store in original containers.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Packaging as recommended by manufacturer.
Storage incompatibility	▶ Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA


Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Trimethyl-1,3-pentanediol monoisobutyrate, 2,2,4-; (Texanol)	13 mg/m3	140 mg/m3	840 mg/m3
Ingredient	Original IDLH	Revised IDLH		
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available	Not Available		

MATERIAL DATA

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields ▶ Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	Wear general protective gloves, eg. light weight rubber gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	See Other protection below
Respiratory protection	Not usually required. Where the concentration of vapours in the breathing zone approaches or exceeds the "Exposure Standards" respiratory protection is required. Type A Filter of sufficient capacity.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

'Forsberg Clothing Performance Index'.The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

RESENE LUMBERSIDER

Material	CPI
PE/EVAL/PE	A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as 'feel' or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1	-
up to 50	1000	-	A-AUS / Class 1
up to 50	5000	Airline *	-
up to 100	5000	-	A-2
up to 100	10000	-	A-3
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Resene Lumbersider Safety Data Sheet (continued)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Acrylic dispersion		
Physical state	Liquid	Relative density (Water = 1)	1.2-1.4
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7-9	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	1000-1500
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	40-45
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	<50

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).
Ingestion	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models).
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

RESENE LUMBERSIDER	TOXICITY	IRRITATION
	Not Available	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >15200 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Inhalation (rat) LC50: >5.325 mg/l/6h ^[2]	Eyes - Moderate irritant *
	Oral (rat) LD50: 3200 mg/kg ^[2]	Skin - Slight irritant *

Resene Lumbersider Safety Data Sheet (continued)

		Skin (rabbit): mild ***
		Skin: no adverse effect observed (not irritating) ^[1]
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE	Not a skin sensitiser (guinea pig, Magnusson-Kligman) *** Ames Test: negative *** Micronucleus, mouse: negative *** Not mutagenic *** No effects on fertility or foetal development seen in the rat *** * [SWIFT] ** [Eastman] *** [Perstop] The material may be irritating to the eye, with prolonged contact causing inflammation. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).	
Acute Toxicity	✗	Carcinogenicity ✗
Skin Irritation/Corrosion	✗	Reproductivity ✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure ✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure ✗
Mutagenicity	✗	Aspiration Hazard ✗
Legend: ✗ – Data either not available or does not fill the criteria for classification ✓ – Data available to make classification		

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

RESENE LUMBERSIDER	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
2,2,4-trimethyl-1,3-pentenediol monoisobutyrate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	9.552mg/L	3
	EC50	48	Crustacea	>19mg/L	2
	EC50	96	Algae or other aquatic plants	0.789mg/L	3
	NOEC	72	Algae or other aquatic plants	2mg/L	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2,2,4-trimethyl-1,3-pentenediol monoisobutyrate	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
2,2,4-trimethyl-1,3-pentenediol monoisobutyrate	LOW (LogKOW = 2.9966)

Mobility in soil

Ingredient	Mobility
2,2,4-trimethyl-1,3-pentenediol monoisobutyrate	LOW (KOC = 22.28)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ Recycle wherever possible or consult manufacturer for recycling options. Consult manufacturer for recycling option. Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.
-------------------------------------	---

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Resene Lumbersider Safety Data Sheet (continued)

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017

2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

GESAMP/EHS Composite List - GESAMP Hazard Profiles	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
IMO IBC Code Chapter 17: Summary of minimum requirements	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
New Zealand - NZIoC	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	11/02/2020
Initial Date	15/03/2018

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Powered by AuthorITe, from Chemwatch.

Resene Clearcote UVS Paint

Waterborne U.V. Protective Glaze

Resene Clearcote UVS is based on a unique acrylic-urethane emulsion for ease of application and maximum life over painted surfaces.

Formulated with U.V. absorbers, Resene Clearcote UVS filters out harmful U.V. light, protecting the underlying coloured coat. Ideally suited for direct application to freshly painted exterior bright organic hues and shades to aid colour retention by protecting these more vulnerable pigments against fading.

	PHYSICAL PROPERTIES
Vehicle type	Acrylic-urethane
Pigmentation	None
Solvent	Water
Finish	Gloss
Dry time (min)	45 minutes at 18°C
Recoat time (min)	2 hours
Primer required	No, always applied over prepainted surface
Theoretical coverage	12 sq. metres per litre
Dry film thickness	26 microns at 12 sq. metres per litre
Usual no. of coats	1
Abrasion resistance	Very good
Chemical resistance	Good
Heat resistance	Good
Solvent resistance	Good
Durability	Excellent
Thinning and clean up	Water
VOC	c. 59 grams per litre (see Resene VOC Summary)

Performance and limitations

PERFORMANCE

- Excellent U.V. protection of the underlying paint surface.
- Designed for application with excellent adhesion over Resene pigmented exterior waterborne topcoats.
- Acid and alkali resistant - inhibits mould growth.
- An Environmental Choice approved product

LIMITATIONS

- Do not apply over solventborne paint finishes.
- Will not penetrate or reinforce weak surfaces.

Resene Clearcote UVS (continued)

Surface preparation

- **All freshly painted surfaces**
 - Ensure surface is clean and dry, free from dirt, dust and loose material, oil, grease and mould.
- Application

Application

- Apply by brush, roller or airless spray.

For more information please visit: www.resene.com

View Data Sheets online at www.resene.com/datasheets

Precautions

- Ensure the correct primer and/or sealer and topcoat is used.
- Do not apply in direct hot sunlight.
- Excessive film builds caused by spreading rates lower than those recommended may cause undesirable milkiness.
- Galvanised steel and Zincalume must be primed and painted before application of Resene Clearcote UVS.

BELOW - Inside of Resene Clearcote brochure

net contents 1 litre LL28401B 4/14

WARNING

Read label before use. Keep out of reach of children. Harmful if swallowed. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/SPRAYS/VAPOURS.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves/protective clothing/eye and face protection. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Rinse mouth. Seek medical attention immediately. Further information available on the SDS.

IF INHALED: If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.

IF ON SKIN (or hair): Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.

IF IN EYES: If this product comes in contact with the eyes, wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: UV Absorbers 10-15 gms/L, Fungicide < 10 gms/L. For use as a decorative/protective coating.

For full technical instructions see Data Sheet D502.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Clearcoat UVS is based on a unique acrylic-urethane for ease of application and maximum life over painted surfaces. Formulated with U.V. absorbers, Resene Clearcoat UVS filters out harmful U.V. light, protecting the underlying coloured coat. Ideally suited for direct application to freshly painted bright organic hues and shades to aid colour retention by protecting these more vulnerable pigments against fading.

Preparation

• Ensure surfaces to be painted are in sound condition, dry, free from dirt, dust and loose material.

• Oil and grease must be removed using Resene Paint Prep and Housewash (see Data Sheet D812). If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry must be treated (see Data Sheet D83).

• **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old asbestos containing building materials may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or Reseller.

Application

• To avoid foaming of material, do not shake and do not brush excessively. Stir well with a wide flat stirrer prior to application.

• Allow at least two hours between coats.

• Do not apply in direct sunlight.

• Do not apply over solventborne paint finishes.

• Not recommended for exterior tile or decorative aggregate flooring where ponding occurs.

Maintenance

(after a minimum of four weeks' drying)

See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Quick check

Use on: Exposed colours that may be prone to fading. Not for use on opening sashes and doors. Do not apply over solventborne paint finishes.

Gloss level: Gloss.

Coverage: 12 square metres per litre per coat. Coverage will vary dependent upon surface porosity and profile.

Dry time (minimum): 45 minutes at 18°C. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 2 hours.

Usual number of coats: 1.

Application method: Brush, roller (Resene No.10 Waterborne Clears sleeve) or airless spray.

Thinning and clean up: Water. In hot conditions may be thinned with up to 5% Resene Hot Weather Additive to slow drying.

Colour range: Clear.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



Clearcoat SDS



Clearcoat TDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using U.V. inks ensuring no emissions.

Resene Clearcote UVS (continued)

Resene Clearcote UVS Safety Data Sheet

RESENE CLEARCOTE UVS

Resene Paints Ltd

Version No: 3.7

Safety Data Sheet according to HSNO Regulations

Issue Date: 28/04/2020

Print Date: 30/04/2020

L.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	RESENE CLEARCOTE UVS
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	9790
--------------------------	------

Details of the supplier of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 2 9186 1132


Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification [1]	Acute Aquatic Hazard Category 3, Skin Sensitizer Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.5B (contact), 9.1D

Label elements

Hazard pictogram(s)	
SIGNAL WORD	WARNING

Hazard statement(s)

H402	Harmful to aquatic life.
H317	May cause an allergic skin reaction.

Precautionary statement(s) Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

Resene Clearcote UVS Safety Data Sheet (continued)

P321	Specific treatment (see advice on this label).	
P302+P352	IF ON SKIN: Wash with plenty of water.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
25265-77-4	1-5	<u>2,2,4-trimethyl-1,3-pentanediol monoisobutyrate</u>
41556-26-7	0.1-0.5	<u>bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate</u>
Not Available	1-5	benzotriazol derivatives

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: <ul style="list-style-type: none">▶ Wash out immediately with water.▶ If irritation continues, seek medical attention.▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: <ul style="list-style-type: none">▶ Immediately remove all contaminated clothing, including footwear.▶ Flush skin and hair with running water (and soap if available).▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none">▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none">▶ Immediately give a glass of water.▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

▶ Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents
----------------------	---

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	<ul style="list-style-type: none">▶ Non combustible. Burning release: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Resene Clearcote UVS Safety Data Sheet (continued)

Methods and material for containment and cleaning up

Minor Spills	Control personal contact with the substance, by using personal protective equipment. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean-up.
Major Spills	Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> Avoid unnecessary personal contact, including inhalation. DO NOT allow clothing wet with material to stay in contact with skin
Other information	<ul style="list-style-type: none"> Store in original containers.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> Packaging as recommended by manufacturer.
Storage incompatibility	<ul style="list-style-type: none"> Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Trimethyl-1,3-pentanediol monoisobutyrate, 2,2,4-; (Texanol)	13 mg/m3	140 mg/m3	840 mg/m3
Ingredient	Original IDLH	Revised IDLH		
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available	Not Available		
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	Not Available	Not Available		


OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	D	> 0.1 to ≤ 1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

MATERIAL DATA

1,2-Benzisothiazoline-3-one (BIT) produces sensitising effects and causes skin irritation at concentrations of 0.05%.
 CEL TWA: 0.1 mg/m3; STEL 0.3 mg/m3 total isothiazolinones (Rohm and Haas)
 (CEL = Chemwatch Exposure Limit)
 for dipropylene glycol monomethyl ether:
 The TLV-TWA and STEL recommendations were thought to be sufficiently low to prevent objectionable irritation and provide a considerable safety factor against CNS impairment.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> Safety glasses with side shields.
Skin protection	See Hand protection below

Resene Clearcote UVS Safety Data Sheet (continued)

Hands/feet protection	<ul style="list-style-type: none"> Wear chemical protective gloves, e.g. PVC. NOTE: <ul style="list-style-type: none"> The material may produce skin sensitisation in predisposed individuals. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. <ul style="list-style-type: none"> Butyl rubber gloves Nitrile rubber gloves (Note: Nitric acid penetrates nitrile gloves in a few minutes.)
Body protection	See Other protection below
Other protection	

Respiratory protection

Not usually required. Where the concentration of vapours in the breathing zone approaches or exceeds the “Exposure Standards” respiratory protection is required. Type A Filter of sufficient capacity.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Appearance	Clear to hazy colourless viscous liquid		
Physical state	Liquid	Relative density (Water = 1)	1.01-1.03
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8-9	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	680
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	69
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	59

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION**Information on toxicological effects**

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).
Ingestion	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'.
Skin Contact	Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

Resene Clearcote UVS Safety Data Sheet (continued)

Chronic	Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals. Benzotriazol derivatives are known contact sensitisers.				
RESENE CLEARCOTE UVS	TOXICITY Not Available		IRRITATION Not Available		
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	TOXICITY Dermal (rabbit) LD50: >15200 mg/kg ^[2] Inhalation (rat) LC50: >5.325 mg/l/6h ^[2] Oral (rat) LD50: 3200 mg/kg ^[2]		IRRITATION Eye: no adverse effect observed (not irritating) ^[1] Eyes - Moderate irritant * Skin - Slight irritant * Skin (rabbit): mild *** Skin: no adverse effect observed (not irritating) ^[1]		
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	TOXICITY Oral (rat) LD50: 3100 mg/kg ^[2]		IRRITATION Not Available		
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances				
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE	Not a skin sensitiser (guinea pig, Magnusson-Kligman) *** Ames Test: negative *** Micronucleus, mouse: negative *** Not mutagenic *** No effects on fertility or foetal development seen in the rat *** * [SWIFT] ** [Eastman] *** [Perstop] The material may be irritating to the eye, with prolonged contact causing inflammation. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).				
RESENE CLEARCOTE UVS & BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL)SEBACATE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema.				
Acute Toxicity	✗		Carcinogenicity	✗	
Skin Irritation/Corrosion	✗		Reproductivity	✗	
Serious Eye Damage/Irritation	✗		STOT - Single Exposure	✗	
Respiratory or Skin sensitisation	✓		STOT - Repeated Exposure	✗	
Mutagenicity	✗		Aspiration Hazard	✗	
Legend: ✗ – Data either not available or does not fill the criteria for classification ✓ – Data available to make classification					
SECTION 12 ECOLOGICAL INFORMATION					
Toxicity					
RESENE CLEARCOTE UVS	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	9.552mg/L	3
	EC50	48	Crustacea	>19mg/L	2
	EC50	96	Algae or other aquatic plants	0.789mg/L	3
	NOEC	72	Algae or other aquatic plants	2mg/L	2
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	=0.34mg/L	1
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				
for propylene glycol ethers: Environmental fate: Most are liquids at room temperature and all are water-soluble. The isothiazolinones are very toxic to marine organisms (fish, Daphnia magna and algae) The high water solubility and low log Kow values of several chlorinated and non-chlorinated indicate a low potential for bioaccumulation. DO NOT discharge into sewer or waterways.					
Persistence and degradability					

Resene Clearcote UVS Safety Data Sheet (continued)

Ingredient	Persistence: Water/Soil	Persistence: Air
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (LogKOW = 2.9966)

Mobility in soil

Ingredient	Mobility
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (KOC = 22.28)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<div><div>Containers may still present a chemical hazard/ danger when empty.</div><div>Legislation addressing waste disposal requirements may differ by country, state and/ or territory.</div><div><div><div>DO NOT allow wash water from cleaning or process equipment to enter drains.</div><div>Recycle wherever possible or consult manufacturer for recycling options.</div></div><div>Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.</div></div></div>
------------------------------	--

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017

2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Approved Hazardous Substances with controls	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals	New Zealand Inventory of Chemicals (NZIoC)

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL)SEBACATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)
--

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Resene Clearcote UVS Safety Data Sheet (continued)

Class of substance	Quantities
Not Applicable	Not Applicable
Refer Group Standards for further information	
Tracking Requirements	
Not Applicable	
National Inventory Status	
National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (2,2,4-trimethyl-1,3-pentanediol monoisobutyrate; bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate; benzotriazol derivatives)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	28/04/2020
Initial Date	02/10/2015

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

Powered by AuthoriTe, from Chemwatch.



Induction Form



This checklist is designed to help you, the registered Artforce participant, ensure that you have received and reviewed all of the relevant materials prior to commencing your Artforce project.

Please take some time to review your starter pack, including the safety information provided. Once you are satisfied with your review please confirm your understanding by ticking off each item on the check list and signing below.

Registered Participant:

Box Number and Location:



Safety Documents:

Tick ☒ to confirm understanding

- ☐ Painting Procedures
- ☐ Emergency Procedures
- ☐ Safety Information – Risk Assessment
- ☐ Site-Set Up Diagram
- ☐ Paint and Cleaner Product and Safety Data Sheets
- ☐ Pre-Start Safety Checklist
- ☐ Manual Handling Guide
- ☐ Covid 19 Direction
- ☐ Incident Reporting Form

Provided Materials:

Tick ☒ to confirm receipt

- ☐ High visibility safety vest
- ☐ Safety cones x 4 (TSB) x 6 (EPT)
- ☐ High quality water-based paint (2.75L TSB; 8L EPT)
- ☐ UV Clearcote (750ml TSB; 2L EPT)
- ☐ Mixing palette
- ☐ Mixing containers x 4
- ☐ Paint prep cleaning agent
- ☐ Masking tape
- ☐ Drop sheets x 4 (TSB) x 6 (EPT)
- ☐ Tack cloth
- ☐ Rags x 2
- ☐ Sanding block and paper
- ☐ Scraper
- ☐ Glue removal product
- ☐ Acetate sheet x 2 (TSBs only)
- ☐ Document wallet containing:
 - o Artforce Manual
 - o Induction Form
 - o Pre-start Safety Checklist
 - o Image Release Form
 - o Feedback Survey
 - o Authority to Paint Notice
- ☐ Mobile equipment box x 1 (TSB) x 2 (EPT)
- ☐ Work-in-Progress Notice
- ☐ Artforce Brisbane t-shirt



Initial Site Visit:

After reviewing all of the provided documentation and equipment, proceed to conducting your initial site visit to familiarise yourself with the area and gather the following information:

Box location:

Box ID:

Does the Box ID number and address match the advice from the Artforce Coordinator?

Yes

No

Box distance from kerb is at least 1.5m?

Yes

No

Box condition:

Yes

No

- ☐ rust holes
- ☐ physical damage
- ☐ open doors
- ☐ any shocks or "tingles" when near or touching the cabinet
- ☐ other condition issues noted

Yes


No

Can a work area can be created without blocking the pedestrian thoroughfare?

☐

☐

Other hazards Identified?



HAZARD Examples

Motion / Mechanical / Electrical / Pressure / Temperature / Chemical / Biological / Radiation / Sound /

Name:

Signature:

Date:



Please **return** this completed induction form to Artforce Brisbane before commencing painting.



Pre-Start Safety Checklist



This checklist is designed to help you, the registered Artforce Brisbane participant, work outside safely, reducing your exposure to health and safety risks and other hazards.

Please take a moment to complete this checklist each time you arrive at your box to start working and at any time when there is a significant change to the working conditions (e.g. weather event).

Date and time:	
Box ID and location:	
Participants:	

BEFORE PAINTING	YES	NO
Is the main registered participant on site and supervising all others?		
Have all participants read and understood these Information Sheets contained in the Artforce Brisbane Manual? <ul style="list-style-type: none"> • Safety Information – Risk Assessment • Paint and Cleaner Product and Safety Data Sheets • Painting Procedures • Emergency Procedures • Site-Set Up Diagram • Manual Handling Guide • Covid 19 Direction 		
Is the box you are painting at least 1.5 metres from the roadside kerb?		
Is the box you are painting in good condition (i.e. no rust holes, physical damage, open doors or any shocks or “tingles” when near or touching the cabinet)?		
Can you set up your work space without blocking the pedestrian thoroughfare?		
Are the weather conditions suitable for work to be conducted safely (e.g. too hot or storm approaching)?		

BEFORE PAINTING	YES	NO
Are lighting conditions adequate for work to be conducted safely?		
Do you have your Authority to Paint Notice?		
Are you familiar with the Emergency Procedures?		
Do you think it is safe to work around your box? This means that there are NO other hazards or potential safety risks at your work site that haven't already been addressed, for example: Is there broken glass around the box? Is there an ant's nest nearby?		
Are you familiar with the process for reporting hazards, incidents, near misses and injuries?		
Do you have a first aid kit on site?		
Do you understand the work procedures and do you have the necessary equipment to do the work safely?		
Do you have all necessary personal protective equipment (PPE)? <ul style="list-style-type: none"> • High visibility safety vest • Sun safety gear: wide brimmed hat, long sleeve shirt and trousers, closed shoes, sunscreen, sunglasses. • Skin protection (gloves or barrier cream) – optional • Eye protection (glasses) – optional 		
If you answer "No" to any of the questions above, contact the Artforce Coordinator before you start work to help ensure your safety and others.		

Please let us know about any hazards you have identified affecting your workspace and what control measures you have used to work safely.	
HAZARD	CONTROL
Example: litter found at work site	Example: removed to public bin prior to commencing work

AFTER PAINTING	YES	NO
Have you removed all masking from the box (including key hole and ID plates)?		
Are the key hole, ID plates, vents and light sensor free from paint?		
Have you left the worksite free from hazards and litter?		

Please leave this safety checklist in the Equipment Pack for return to Artforce Brisbane after painting is complete.

SAMPLE ONLY –
DO NOT COMPLETE





Still and Moving Image Release Form



Artforce Brisbane participants are encouraged to submit still and/or moving images of work-in-progress and completed artwork with social context, such as images of family and friends painting or posing with the box. Artforce Brisbane wishes to use these images for promotional purposes. Any images which feature identifiable people require the written permission of those people prior to our use.

Please ask any subjects featured in your images to sign this Image Release Form and submit the completed form together with your images to Artforce Brisbane.

TSB or EPT BOX NUMBER AND LOCATION (SUBURB):

PRIMARY ARTFORCE BRISBANE PARTICIPANT:

ARTWORK TITLE:

DATE PAINTED (MONTH & YEAR):

SUBJECT/S GIVING CONSENT:

Subject Name	Name of Parent or Guardian if applicable	Address	Please indicate if you identify as Aboriginal and/or Torres Strait Islander? (✓)

I, the above named subject OR parent or guardian of the above named subject, give my unreserved permission for all still and moving images taken or recorded by or on behalf of or made available to Artforce Brisbane of me ("the images") to be:

- used in the promotional and advertising material of Artforce Brisbane; and/or
- provided to any third party, including but not limited to media organisations, government bodies, not-for-profit organisations and Artforce Brisbane partners, for their use as they see fit.

The images may be used in various media formats including online media, social media, print, newspaper, video, public displays, television, and electronic means of communication, and in any edited form.

I waive any rights and claims, present and future, to any fees or royalties or other benefits whatsoever for or in connection with the use of the images.

If I wish to withdraw permission for images to be used, I must so inform Artforce Brisbane in writing. I understand that if I so withdraw permission for the images to be used, Artforce Brisbane will cease any future new publication or use of the images, but for several years the images may appear in printed and electronic material which has already been produced or disseminated.

(For Aboriginal and Torres Strait Islander people) I also understand that images of Aboriginal and Torres Strait Islanders may appear in printed and electronic material for several years. If I am an Aboriginal or Torres Strait Islander, Artforce Brisbane will take reasonable steps to prevent the images from appearing on material published after my death. However, I understand and agree that, despite those efforts, the images may still be published or disseminated.

I understand that Artforce Brisbane will make all reasonable efforts to ensure that any use of the images by Artforce Brisbane or third parties complies with:

- respect and protect those whose images are recorded in Artforce Brisbane photography;
- manage and use images owned by Artforce Brisbane appropriately

I understand that I have no actionable right against Artforce Brisbane for any failure by either Artforce Brisbane or by any third party to comply with the terms of this release form.

_____ PRINT NAME	_____ SIGNATURE	_____ DATE
_____ PRINT NAME	_____ SIGNATURE	_____ DATE
_____ PRINT NAME	_____ SIGNATURE	_____ DATE
_____ PRINT NAME	_____ SIGNATURE	_____ DATE
_____ PRINT NAME	_____ SIGNATURE	_____ DATE

Feedback Survey





We value your contribution to the Artforce Brisbane program and are keen to receive your feedback. To complete the survey online please go to:

mailchi.mp/artforcebrisbane.com.au/feedbacksurvey

OR

Complete the hard copy form provided in the equipment pack and then either return in your equipment pack or scan and email to

info@artforcebrisbane.com.au



Incident Report Form

Incident details				
Name of person involved in the incident:			Date of incident:	
Location of incident:				
Incident investigation team:				
What task was being performed at the time of the incident?				
What happened? (e.g. 'employee tripped over box' or 'forklift hit wall')				
What factors contributed to the incident?				
Environment:		Equipment/materials:		
<input type="checkbox"/> Noise	<input type="checkbox"/> Layout / design	<input type="checkbox"/> Wrong equipment for the job	<input type="checkbox"/> Equipment failure	
<input type="checkbox"/> Lighting	<input type="checkbox"/> Dust / fume	<input type="checkbox"/> Inadequate maintenance	<input type="checkbox"/> Material / equipment too heavy / awkward	
<input type="checkbox"/> Vibration	<input type="checkbox"/> Slip / trip hazard	<input type="checkbox"/> Inadequate guarding	<input type="checkbox"/> Inadequate training provided	
<input type="checkbox"/> Damaged / unstable floor	<input type="checkbox"/> Other	<input type="checkbox"/> Other		
Work systems:		People:		
<input type="checkbox"/> Hazard not identified	<input type="checkbox"/> No / inadequate risk assessment conducted	<input type="checkbox"/> Procedure not followed / no procedure exists	<input type="checkbox"/> Drugs / alcohol	
<input type="checkbox"/> No / inadequate safe work procedure	<input type="checkbox"/> No / inadequate controls implemented	<input type="checkbox"/> Fatigue	<input type="checkbox"/> Time / production pressures	
<input type="checkbox"/> Hazard not reported	<input type="checkbox"/> Inadequate training / supervision	<input type="checkbox"/> Change of routine	<input type="checkbox"/> Distraction / personal issues / stress	
<input type="checkbox"/> Other		<input type="checkbox"/> Lack of communication	<input type="checkbox"/> Other	
Corrective actions:				
Contributing factor (from above list)	What are we going to do to fix the problem?	Who	When	Completion date
Issue fixed?				
Name	Signature		Date	
Person involved in incident:				
Manager:				

Incident investigation process guide

1. Establish the facts of the incident, including:
 - What happened?
 - When and where did it happen?
 - What task was being done?
 - Who was involved?
 - Were there any witnesses?
2. Gather all necessary background information, for example:
 - maintenance records
 - safe work procedures
 - instructions manuals
 - training records.
3. Consider all the potential contributing factors:
 - Environment: *Did environmental conditions (e.g. light, noise, floor surfaces) contribute to the incident?*
 - Equipment /materials: *Did anything about the equipment, materials, tools etc (e.g. equipment failures, missing guards) contribute to the incident?*
 - Work systems: *Was there something about the system that contributed (e.g. hazard not identified, known hazard not addressed)?*
 - People: *Was there something the workers, supervisors or contractors did that contributed to the incident (e.g. poor communication, being tired or rushing to finish on time)?*
4. Determine the primary cause/s of the incident, that is, those which if they hadn't occurred then the incident wouldn't have occurred. Ask yourself "*Would the incident have happened if....?*"
5. Identify the root cause / system failures that underlie the primary cause/s and contributing factors.

One simple technique for identifying the root cause is the 'Five Whys'. This technique involves asking yourself 'Why did this happen?' and continuing to ask 'Why' for each response until you reach a conclusion that does not generate another 'why' and the underlying cause becomes apparent.
6. The final and most important step in any investigation is to take action to fix all the factors that contributed to the incident, starting with the primary cause/s and working through each of the contributing and underlying causes.

Authority to Paint Notice



This will be supplied when we provide you with your pack.



We are pleased to have your participation in the Artforce Brisbane program. This letter verifies details of your allocated Box, approved painting dates and the date and location your Equipment Pack will be delivered.

Approved Artforce participant name:	Arty Person
Box Number & Location:	B0101 – Streety St & Roady Rd, Suburbia QLD 4000
Approved Artwork:	Brisbania
Date of Dispatch of Equipment Pack:	Date (collection from the next day)
Equipment Delivered to:	Ward Office name Ward Office address Phone: Ward office phone number
Approved Painting Dates:	Friday X Month – Monday X Month 202X

Your Equipment Pack contains most of the equipment you will need to paint the Box and a printed copy of the Artforce Brisbane Manual. Please read the Manual before you commence painting.

When you have finished painting, please:

1. Take and submit photos of your painted Box. Refer to the Artwork Photo Guide information in the Artforce Brisbane Manual.
2. Complete the Feedback Survey at <https://mailchi.mp/artforcebrisbane.com.au/feedbacksurvey> or in the hard copy provided.
3. Ensure that all the equipment and completed forms are securely packed into the Equipment Pack and the lid is secure. Then return the Equipment Pack to the same place it was delivered. Please do this as soon as possible and no longer than 5 days after you have completed painting. If you experience any delays, please contact us.
4. Please notify Artforce via email when the Pack is ready for collection.

If you have any questions, please don't hesitate to call. Have a great time painting and keep safe.

Kind regards

Susan Lincoln
Artforce Coordinator

Artforce Brisbane

0428 095 939
info@artforcebrisbane.com.au
artforcebrisbane.com.au

An initiative of



Dedicated to a better Brisbane



An initiative of



Dedicated to a better Brisbane